

## Description

Yealink SIP-T23G features intuitive user interface and enhanced functionality which make it easy for people to interact and maximize productivity. Yealink HD technology enables rich, clear, life-like voice communications, outsourced management options, flexible deployment and third-party communications applications. As a cost effective IP solution, it helps users to streamline business processes, delivery a powerful, security and consistent communication experience for small and large offices environment

## Features

- Yealink HD voice
- Dual- Port Gigabit Ethernet
- 132x64 pixel graphical LCD
- Support Dual Color LEDs
- Up to 3 SIP accounts
- Paperless design
- PoE support
- Headset, EHS support
- Simple, Flexible and secure provisioning options

## Specification

### Audio Features

- HD voice: HD handset, HD speaker
- Wideband Codecs: Opus, G.722
- Narrowband Codes: Opus\*, G.711(A/μ), G.729, 729AB, G.726, iLBC
- DTMF: In-band, Out-of-band(RFC 2833) and SIP INFO
- Full-duplex hands-free speakerphone with AEC
- VAD, CNG, PLC, AJB, AGC

### Phone Features

- 3 SIP account
- Call hold, mute, DND
- One Touch speed dial, hotline
- Call forward, call waiting, call transfer
- Group listening, SMS, emergency call
- Redial, call return, auto answer
- Local 3-way conferencing
- Direct IP call without SIP proxy
- Ring tone selection/import/delete
- Set date time manually or automatically
- Dial plan
- XML Browser
- Action URL/URI

- Integrated screenshots
- RTCP-XR

#### Directory

- Local phonebook up to 1000 entries
- Black list
- XML/LDAP remote phonebook
- Intelligent search method
- Phonebook search/import/export
- Call history: dialed/received/missed/forwarded

#### IP-PBX Features

- Busy Lamp Field (BLF)]
- Bridged Line Appearance(BLA)]
- Anonymous call, anonymous call rejection
- Hot-desking, voice mail
- Music on hold
- Message Waiting Indicator (MWI)
- Call park, call pickup
- Intercom, paging
- Call completion, call recording

#### Display and Indicator

- 132x64-pixel graphical LCD with backlight
- LED for call and message waiting indication
- Dual-color (red or green) illuminated LEDs for line status information
- Wallpaper
- Multilingual user interface with icons and soft keys
- Caller ID with name, number and photo

#### Feature keys

- 3 line keys with LED
- 5 features keys: message, headset, redial, hands-free speakerphone
- 6 navigation keys
- Volume control keys

#### Interface

- Dual-port Gigabit Ethernet
- 1xUSB 2.0 port
- 1xRJ9 (4P4C) handset port
- 1xRJ9 (4P4C) headset port

### Other Physical Features

- Wall mountable
- External universal AC adapter (optional): AC 100~240V input and DC 5V/600mA output
- Power consumption (PSU): 0.72-1.56W
- Power consumption (PoE): 0.96-1.98W
- Dimension(W\*D\*H\*T):209mm\*188mm\*150.5mm\*41mm
- Operating humidity: 10~95%
- Operating temperature: -10~50°C

### Management

- Configuration: browser/phone/auto-provision
- Auto provision via FTP/TFTP/HTTP/HTTPS for mass deploy
- Auto-provision with PnP
- Broadsoft device management
- Zero-sp-touch, TR-069
- Phone lock for personal privacy protection
- Reset to factory, reboot
- Package tracing export, system log

### Network and Security

- SIP v1 (RFC2543), v2 (RFC3261)
- IPv6
- NAT transverse: STUN mode
- Proxy mode and peer-to-peer SIP link mode
- IP assignment: static/DHCP
- HTTP/HTTPS web server
- Time and date synchronization using SNTP
- UDP/TCP/DNS-SRV(RFC 3263)
- QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS, DSCP
- SRTP for voice
- Transport Layer Security (TLS)
- HTTPS certificate manager
- AES encryption for configuration file
- Digest authentication using MD5/MD5-sess
- OpenVPN, IEEE802.1X

### Others

- **Warranty: 2 Years ( Local - Singapore) Includes Free Email Support**
- **Lead Time: 1 to 3 Weeks**
- **Package Features**

#### Package Features

- > Qty/CTN: 10 PCS
- > G.W/CTN: 12.6kg
- > Giftbox size: 215mm\*200mm\*118mm
- > Carton Meas: 615mm\*436mm\*208mm

• **Carton Model:** 60mm x 60mm x 200mm